

















Non-Connected Thermostats

Image	Description	Model	Scheduling	User Interface	Application					Power Method	Sensors				Display Information		Limited Warranty	Wiring Terminals	Accessories Included					
					Stages	Gas, Oil or Electric	Heat Pump	Millivolt	Linevolt		Permanent Memory Retention	Selectable Auto or Manual Changeover	Dual Fuel	Wired Outdoor Sensor	Wired Indoor Sensor	Floor / Slab Sensor				Temperature Setpoint Limits	Display Size (Viewable)	On Demand Backlighting		
	T6 Pro	TH6320U2008	7-Day, 5-1-1, 5-2, or NP	Soft keys	Up to 3 Heat/2 Cool – Heat Pump Up to 2 Heat/2 Cool – Conventional	•	•	•			Dual powered (battery and hardwire)	•	•	•	Lockouts only, no display	•		•	5.44 sq. in.	•	5 Year	R, RC, C, W, W2-AUX, Y, Y2, G, L, K, S and S, O/B, and E and S	UWP mounting system, decorative cover plate, mounting hardware & batteries	
		TH6220U2000	7-Day, 5-1-1, 5-2, or NP	Soft keys	Up to 2 Heat/1 Cool – Heat Pump Up to 2 Heat/2 Cool – Conventional	•	•	•			Dual powered (battery and hardwire)	•	•	•	Lockouts only, no display	•		•	5.44 sq. in.	•	5 Year	R, RC, C, W, W2-AUX, Y, Y2, G, L, K, S and S, O/B, and E and S	UWP mounting system, decorative cover plate, mounting hardware & batteries	
		TH6210U2001	7-Day, 5-1-1, 5-2, or NP	Soft keys	Up to 2 Heat/1 Cool – Heat Pump Up to 1 Heat/1 Cool – Conventional	•	•	•			Dual powered (battery and hardwire)	•	•						•	5.44 sq. in.	•	5 Year	R, RC, C, W, W2-AUX, Y, G, L, O/B, E and K	UWP mounting system, decorative cover plate, mounting hardware & batteries
	T6 Pro Hydronic	TH6100AF2004	7-day, 5-1-1, 5-2, or NP	Soft keys	1 Stage Hot Water Heat Only – No Fan						Dual powered (battery and hardwire)	•						•	5.44 sq. in.	•	5 Year	R, RC, C, W, S, and S	Floor sensor, UWP mounting system, decorative cover plate, mounting hardware & batteries	
	T4 Pro	TH4210U2002	7-day, 5-1-1, 5-2, or NP	Soft keys	Up to 2 Heat/1 Cool – Heat Pump Up to 1 Heat/1 Cool – Conventional	•	•	•			Dual powered (battery and hardwire)	•	•					•	3.93 sq. in.	•	5 Year	R, RC, C, W, W2-AUX, Y, G, L, O/B, E & K	UWP mounting system, decorative cover plate, mounting hardware & batteries	
		TH4110U2005	7-day, 5-1-1, 5-2, or NP	Soft keys	Up to 1 Heat/1 Cool – Heat Pump Up to 1 Heat/1 Cool – Conventional	•	•	•			Dual powered (battery and hardwire)	•	•						•	3.93 sq. in.	•	5 Year	R, RC, W, O/B, Y, G, C, L, and K	UWP mounting system, decorative cover plate, mounting hardware & batteries
	TL8100 Hydronic	TL8100A1008	7-Day	Soft keys	Control a line Voltage (120/240VAC) valve or pump or a 24 volt valve.	Gas or oil			•		Battery powered	•							2.67 sq. in.	•	5 Year	1, 2, 3	Mounting hardware & Batteries	
	T3 Pro Non-Programmable	TH3210U2004	NP	Soft keys	2 Heat/1 Cool – Heat Pump 1 Heat/1 Cool – Conventional	•	•	•			Dual powered (battery and hardwire)	•	•					•	3.32 sq. in.	•	5 Year	R, RC, C, W, O/B, Y, G, AUX, and E	UWP mounting system, decorative cover plate, mounting hardware & batteries	
		TH3110U2008	NP	Soft keys	1 Heat/1 Cool – Heat Pump 1 Heat/1 Cool – Conventional	•	•	•			Dual powered (battery and hardwire)	•	•						•	3.32 sq. in.	•	5 Year	R, RC, C, W, O/B, Y, and G	UWP mounting system, decorative cover plate, mounting hardware & batteries
	Pro 3000 Non-Programmable	TH3210D1004	NP	Soft Keys	2 Heat/1 Cool – Heat Pump only	•	•				Dual powered (battery and hardwire)	•	Manual					•	1.32 sq. in.	•	5 Year	R, C, O, B, Y, G, L, AUX, and E.	Mounting hardware & Batteries	
		TH3110D1008	NP	Soft Keys	1 Heat/1 Cool – Heat Pump 1 Heat/1 Cool – Conventional	•	•	•			Dual powered (battery and hardwire)	•	Manual						•	1.32 sq. in.	•	5 Year	R, RC, C, O, B, Y, W, and G.	Mounting hardware & Batteries
	T1 Pro Non-Programmable	TH1110D2009	NP	Soft Keys	1 Heat/1 Cool – Heat Pump 1 Heat/1 Cool – Conventional	•	•	•			Dual powered (battery and hardwire)	•	Manual					•	2.37 sq. in.	•	5 Year	C, R, RC, W, O/B, Y, G	UWP mounting system, decorative cover plate, mounting hardware & batteries	
		TH1010D2000	NP	Soft Keys	1 Heat or 1 Cool	•	•				Dual powered (battery and hardwire)	•	Manual						•	2.37 sq. in.	•	5 Year	C, R, RC, W, Y, G	UWP mounting system, decorative cover plate, mounting hardware & batteries
	E1 PRO Non-Programmable	TH1110E1000	NP	Softkeys	1 Heat/1 Cool – Heat Pump 1 Heat/1 Cool – Conventional	•	•	•			Dual powered (battery and hardwire)	•	Manual						3.32 sq. in.	•	2 Year	R, RC, C, W, Y, G, O, and B	Wall-plate, mounting hardware, & batteries	
	The Digital Round™	T8775A1009	NP	Dial	1 Heat	•					Power stealing	•							.75 sq. in.	•	5 Year	R, W	Mounting hardware	
		T8775C1005	NP	Dial	1 Heat/1 Cool	•						Power stealing	•	Manual						.75 sq. in.	•	5 Year	R, RC, W, O, B, Y, G	Mounting hardware
	The Round™	T87K1007	NP	Dial	1 Heat or 1 Cool	•					Power stealing								50010944-001	N/A	5 Year	R, W, Y	Mounting hardware	
		T87N1000	NP	Dial	1 Heat/1 Cool	•						Power stealing		Manual					50010944-001	N/A	5 Year	R, RC, W, Y, G, O, B	Mounting hardware	
		T87N1026	NP	Easy-To-See™	1 Heat/1 Cool	•						Power stealing		Manual						50010944-001	N/A	5 Year	R, RC, W, Y, G, O, B	Mounting hardware
		T834N1002 Vertical	NP	Slide switches and lever	1 Heat/1 Cool	•					Mechanical		Manual						50019661-001	N/A	5 Year	R, RC, W, Y, G, O, B	Mounting hardware	
		T8034N1007 Horizontal	NP	Slide switches and lever	1 Heat/1 Cool	•						Mechanical		Manual						50019661-001	N/A	5 Year	R, RC, W, Y, G, O, B	Mounting hardware
		T822K1000	NP	Slide switches and lever	1 Heat	•					Mechanical		Positive off						50019661-001	N/A	5 Year	R, W	Mounting hardware	
		T822K1018	NP	Slide switches and lever	1 Heat	•						Mechanical		Positive off						50019661-001	N/A	5 Year	R, W	Mounting hardware
		T827K1009	NP	Slide switches and lever	1 Heat	•		•				Mechanical		Positive off						50019661-001	N/A	5 Year	R, W	Mounting hardware
	TL8230	TL8230A1003	7-Day	Soft keys	1 Heat				•		3328 watts @ 208 VAC Max 3840 watts @ 240 VAC Max	•	Positive off						2.67 sq. in.	•	5 Year	4-wire DPST	Mounting hardware	
		TL7235A1003	NP	Horizontal lays	1 Heat				•		3600 watts @ 240 VAC Max 3120 watts @ 208 VAC Max	•	Positive off						2.67 sq. in.	•	3 Year	4-wire DPST	Mounting hardware	
		T410A1013 T410A1021 T410B1004	NP	Dial	1 Heat				•		22A at 120/208/240 VAC Max, 19A at 277 VAC Max		T410B has positive off						N/A		3 Year	T410A - 2-wire SPST T410B - 4-wire DPST	Mounting hardware	
		TH105PLUS	5-2	Buttons	1 Heat				•		3500 watts @ 240 VAC Max 1700 watts @ 120 VAC Max	•									3 Year	2-wire SPST	Mounting hardware	

50-1376 | V N | 08/20
© 2020 Resideo Technologies, Inc. All rights reserved. The Honeywell Home trademark is used under license from Honeywell International, Inc. These products are manufactured by Resideo Technologies, Inc., and its affiliates.