


# New Point-Of-Use Codes Are Here

New plumbing code changes for the International Plumbing Code (IPC), Uniform Plumbing Code (UPC) and the National Standard Plumbing Code (NSPC) require the control of Domestic Hot Water (DHW) through the use of thermostatic mixing valves.

- All sinks and non-shower bathtubs must use a thermostatic mixing valve that conforms to the new ASSE 1070 standard. Maximum water temperature allowed is 120° F.
- All public facilities with lavatories and bidets are also included. Maximum water temperature allowed is 110° F.

## New AM-1 1070 SERIES and UMV-304U Thermostatic Mixing Valves

Meet The New 2006 Plumbing Code Requirements For Point-Of-Use Applications



STAY AHEAD OF NEW PLUMBING CODES AND PERFORMANCE STANDARDS

## ASSE 1070 Approved Thermostatic Mixing Valves

### Automation and Control Solutions

Honeywell  
1985 Douglas Drive North  
Golden Valley, MN 55422-3992  
1-800-468-1502  
yourhome.honeywell.com



63-9705  
October 2009  
© 2009 Honeywell International Inc.

# Honeywell Has You Covered With ASSE 1070 Approved Mixing Valves

Many state and local approval agencies are in the process of adopting the new plumbing codes and ASSE Performance Standards. To help you be ready for the change, Honeywell has thermostatic mixing valves models available now that conform to the new ASSE 1070 standard.



## New AM-1 1070 SERIES

- ASSE 1070 certified.
- Union body style models with flow rates up to 10 gpm.



## UMV-304U

- Dual-listed for ASSE 1070 and ASSE 1016.
- Designed for individual fixture usage with flow rates up to 3 gpm.
- Universal model for 3- or 4-port applications.

These new generation products incorporate a lockable, black hand-wheel and updated product identification labels that indicate the new ASSE 1070 listing.

## ASSE 1070 Is Here To Stay

This original ASSE 1016-T 1996 standard has been split into three separate mixing valve standards based upon application:

Standard	Application
ASSE 1016-2005	For automatic compensating valves for individual showers and tub/shower combinations.
ASSE 1069-2005	For automatic temperature control mixing valves for multiple shower applications.
ASSE 1070-2004	For water temperature limiting devices.

ASSE 1016-T 1996 listings will be valid through June 2009. After that date, the three standards broken out above will be new requirements for point-of-use applications.

**Honeywell is helping you stay ahead of the curve. Start ordering new AM-1 1070 Series and UMV-304U mixing valves today to be ready for code adoption in your area.**



## New AM-1 1070 SERIES Thermostatic Mixing Valve

- **Easy Installation**  
Available in multiple connection types, including new PEX fittings.
- **Color-Coded**  
New black lockable hand-wheel prevents tampering and is required by the new ASSE 1070 standard.
- **Built-In Check Valve**  
Prevents reverse flow of hot water through the cold port and is required by the new ASSE 1070 standard.
- **Teflon® Coating**  
Resists mineral deposit build-up and extends service life.
- **High CV Rating** of 1.8.
- **ASSE 1070 Approved**  
For point-of-use requirements.



## Free Thermostrip® Included

Makes temperature setting easy for one person to handle.